

بيكسل x 1080 شاشة حاسوب مسطحة 58,4 سم (23") x 1080 سيكسل x 1080 شاشة حاسوب مسطحة للكوء LED أسود

C6Y18A4 : العلامة التجارية

ZR2330w : اسم المنتج

HP ZR2330w 23-inch IPS LED Backlit Monitor

كامل, تقنية الشاشة: HD: HD بيكسل, نوع 1080 x قطر الشاشة: 58,4 سم (23"), وضوح العرض: 1920 HP ZR2330w. 1920 نرمن الاستجابة: 14 مللي ثانية, نسبة الأبعاد الأصلية: 16:9, زاوية الرؤية، أفقياً: 178 درجة, زاوية , عمودياً: 178 درجة. نسخة موزع تعديل الارتفاع. لون المنتج: أسود 2.0. USB: 2.0 الرؤية، عمودياً: 178





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Touchscreen * Display brightness (typical) Response time * Supported graphics resolutions	58.4 cm (23") 1920 x 1080 pixels Full HD 16:9 LED IPS X 250 cd/m² 14 ms 1920 x 1080 (HD 1080) 16:9	Height adjustment * Pivot Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play LED indicators	 7 7 0 - 360° 7 -5 - 30° 7 7
Aspect ratio		Power	
Contrast ratio (typical) * Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Pixel pitch 3D	1000:1 1000000:1 178° 178° 0.265 x 0.265 mm	Power consumption (typical) * Power consumption (standby) * Power consumption (max) AC input voltage Operational conditions	35 W 0.5 W 40 W 100 - 240 V
Multimedia		Operating temperature (T-T) Operating relative humidity (H-H)	5 - 35 °C 20 - 80%
Built-in speaker(s) * Built-in camera * Design Product colour *	X X Black	Weight & dimensions Width (with stand) Depth (with stand) Height (with stand)	551.5 mm 249.4 mm 467 mm
Ports & interfaces	Didek	Width (without stand)	551.5 mm
USB hub version USB Type-A downstream ports quantity	2.0	Depth (without stand) Height (without stand) Weight (without stand)	49.5 mm 334.2 mm 4.1 kg
VGA (D-Sub) ports quantity DVI-D ports quantity DisplayPorts quantity	1 1 1	Sustainability Sustainability certificates	EPEAT Silver, ENERGY STAR

Ports & interfaces		Other features	
AC (power) in	✓	Country of origin	China
Ergonomics		TV tuner integrated	×
Panel mounting interface	100 x 100 mm ✓	Certification	TCO
Cable lock slot *		Thin Client	
		Thin client installed	×




















































































Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.