

ATGBICS CAB-D-D-400G-2.5M Arista Compatible Direct Attach Copper Cable 400GBase-CU QSFP-DD (Passive Twinax 2.5m)

Brand : ATGBICS

Product code: CAB-D-D-400G-2.5M-C

Product name : CAB-D-D-400G-2.5M Arista Compatible Direct Attach Copper Cable 400GBase-CU QSFP-DD (Passive Twinax 2.5m)

CAB-D-D-400G-2.5M Arista Compatible Direct Attach Copper Cable 400GBase-CU QSFP-DD (Passive Twinax 2.5m)

ATGBICS CAB-D-D-400G-2.5M Arista Compatible Direct Attach Copper Cable 400GBase-CU QSFP-DD (Passive Twinax 2.5m):

ATGBICS Arista Compatible CAB-D-D-400G-2.5M 400GBase-CU QSFP-DD to QSFP-DD Passive Direct Attach Cable operates over Passive Copper with a cable length of 2.5m. This product operates within a commercial temperature range. It is suitable for short reach connection between two QSFP-DD ports in 400G interconnecting networking applications. Our product meets the specification of Arista CAB-D-D-400G-2.5M and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols. ATGBICS CAB-D-D-400G-2.5M Arista Compatible Direct Attach Copper Cable 400GBase-CU QSFP-DD (Passive Twinax 2.5m). Cable length: 2.5 m, Cable type: DAC, Connector 1: QSFP-DD, Connector 2: QSFP-DD



Features		Features	
Cable length *	2.5 m	Brand compatibility	Arista
InfiniBand protocol	✓	Plug and Play	✓
AWG wire size	26	Sustainability	
Cable shape	Round	Doesn't contain	Lead
Fastening type	Push-pull	Certificates	
Connector 1 *	QSFP-DD	Compliance certificates	TÜV mark, UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
Connector 2 *	QSFP-DD	Certification	CE, FCC, RoHS, REACH, FDA, TUV
Connector 1 gender *	Male	Operational conditions	
Connector 2 gender *	Male	Operating temperature (T-T)	0 - 70 °C
Cable type *	DAC	Storage temperature (T-T)	-40 - 85 °C
Product colour *	Black	Weight & dimensions	
Ethernet interface type	400 Gigabit Ethernet	Bending radius	3.3 cm
Data transfer rate	400000 Gbit/s	Packaging content	
Data transfer rate	400000 Mbit/s	Quantity per pack	1 pc(s)
Jacket material *	Optical fiber non-conductive riser (OFNR), Polyvinyl chloride (PVC)	Logistics data	
Conductor material	Copper	Country of origin	United Kingdom

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-MAY-2025. Prints or copies of Information are only valid on the printed Publication date