

# ATGBICS FTLX3671DTC54 Finisar Compatible Transceiver DWDM Ch54 SFP+ 1.2 to 11.3GBase (1534.25nm, SMF, 40km, LC, DOM, Ind Temp)

**Brand :** ATGBICS

**Product code:** FTLX3671DTC54-C

**Product name :** FTLX3671DTC54 Finisar Compatible Transceiver DWDM Ch54 SFP+ 1.2 to 11.3GBase (1534.25nm, SMF, 40km, LC, DOM, Ind Temp)



FTLX3671DTC54 Finisar Compatible Transceiver DWDM Ch54 SFP+ 1.2 to 11.3GBase (1534.25nm, SMF, 40km, LC, DOM, Ind Temp)

ATGBICS FTLX3671DTC54 Finisar Compatible Transceiver DWDM Ch54 SFP+ 1.2 to 11.3GBase (1534.25nm, SMF, 40km, LC, DOM, Ind Temp). SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Brand compatibility: Finisar. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Compliance certificates: RoHS, Certification: CE, FCC, RoHS. Doesn't contain: Lead



Performance		Certificates	
SFP transceiver type *	Fiber optic	Compliance certificates	RoHS
Maximum data transfer rate *	10000 Mbit/s	Certification	CE, FCC, RoHS
Interface type *	SFP+	Sustainability	
Single-mode fiber (SMF) supported	✓	Sustainability compliance	✓
Multi-mode fiber (MMF) supported	✗	Doesn't contain	Lead
Fiber optic connector	LC	Operational conditions	
SFP transceiver standard	DWDM	Minimum operating temperature	-40 °C
Maximum transfer distance	40000 m	Maximum operating temperature	85 °C
Wavelength	1534.25 nm	Operating temperature (T-T)	-40 - 85 °C
Coarse Wavelength Division Multiplexing (CWDM)	✓	Storage temperature (T-T)	-40 - 85 °C
Ethernet LAN	✓	Operating relative humidity (H-H)	0 - 95%
Ethernet interface type	10 Gigabit Ethernet	Storage relative humidity (H-H)	0 - 95%
Digital Diagnostics Monitoring (DDM)	✓	Weight & dimensions	
Features		Width	13.4 mm
Product colour	Silver	Depth	56.5 mm
Housing material	Metal	Height	8.5 mm
Plug and Play	✓	Weight	20 g
Hot-swap	✓	Packaging content	
Easy to install	✓	Quantity per pack	1 pc(s)
Brand compatibility	Finisar	Packaging data	
Power		Package type	Box
Input voltage	3.3 V	Logistics data	
Maximum voltage	3.5 V	Country of origin	United Kingdom
Power consumption (typical)	1 W		



5056468764300

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-OCT-2024. Prints or copies of Information are only valid on the printed Publication date