**ATGBICS**

# ATGBICS FTLX3871MCC29 Finisar Compatible Transceiver DWDM Ch29 SFP+ 10GBase (1554.13nm, SMF, 80km, LC, DOM)

**Brand :** ATGBICS

**Product name :** FTLX3871MCC29 Finisar Compatible Transceiver DWDM Ch29 SFP+ 10GBase (1554.13nm, SMF, 80km, LC, DOM)

**Product code:** FTLX3871MCC29-C

FTLX3871MCC29 Finisar Compatible Transceiver DWDM Ch29 SFP+ 10GBase (1554.13nm, SMF, 80km, LC, DOM)
ATGBICS FTLX3871MCC29 Finisar Compatible Transceiver DWDM Ch29 SFP+ 10GBase (1554.13nm, SMF, 80km, LC, DOM). SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Brand compatibility: Finisar. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Compliance certificates: RoHS, Certification: CE, FCC, RoHS. Doesn't contain: Lead

## Performance

| | |
|---|---|
| SFP transceiver type * | Fiber optic |
| Maximum data transfer rate * | 10000 Mbit/s |
| Interface type * | SFP+ |
| Single-mode fiber (SMF) supported | ✔ |
| Multi-mode fiber (MMF) supported | ✖ |
| Fiber optic connector | LC |
| SFP transceiver standard | DWDM |
| Maximum transfer distance | 80000 m |
| Wavelength | 1554.13 nm |
| Coarse Wavelength Division Multiplexing (CWDM) | ✔ |
| Ethernet LAN | ✔ |
| Ethernet interface type | 10 Gigabit Ethernet |
| Digital Diagnostics Monitoring (DDM) | ✔ |

## Features

| | |
|---|---|
| Product colour | Silver |
| Housing material | Metal |
| Plug and Play | ✔ |
| Hot-swap | ✔ |
| Easy to install | ✔ |
| Brand compatibility | Finisar |

## Power

| | |
|---|---|
| Input voltage | 3.3 V |
| Maximum voltage | 3.5 V |
| Power consumption (typical) | 1 W |

## Certificates

| | |
|---|---|
| Compliance certificates | RoHS |
| Certification | CE, FCC, RoHS |

## Sustainability

| | |
|---|---|
| Sustainability compliance | ✔ |
| Doesn't contain | Lead |

## Operational conditions

| | |
|---|---|
| Minimum operating temperature | -5 °C |
| Maximum operating temperature | 70 °C |
| Operating temperature (T-T) | -5 - 70 °C |
| Storage temperature (T-T) | -40 - 85 °C |
| Operating relative humidity (H-H) | 0 - 95% |
| Storage relative humidity (H-H) | 0 - 95% |

## Weight & dimensions

| | |
|---|---|
| Width | 13.4 mm |
| Depth | 56.5 mm |
| Height | 8.5 mm |
| Weight | 20 g |

## Packaging content

| | |
|---|---|
| Quantity per pack | 1 pc(s) |

## Packaging data

| | |
|---|---|
| Package type | Box |

## Logistics data

| | |
|---|---|
| Country of origin | United Kingdom |

5056468765352