

## ASUS ROG -LOKI-1200T-SFX-L-GAMING power supply unit 1200 W 20+4 pin ATX Black, Silver

**Brand :** ASUS

**Product family:** ROG


**Product code:** 90YE00N0-B0NA00

**Product name :** ROG-LOKI-1200T-SFX-L-GAMING



ROG Loki SFX-L 1200W Titanium fully modular gaming power supply (120mm PWM ARGB fan, Aura Sync ARGB lighting, ATX 3.1 compatible, PCIe 5.0 Ready, incl. 16-pin cable, 80+ Titanium certification, Lambda Standard ++ certification)

ASUS ROG -LOKI-1200T-SFX-L-GAMING. Total power: 1200 W, AC input voltage: 100 - 240 V, Peak power: 1200 W. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 45 cm, SATA power cable length: 100,200,300 mm. Purpose: PC, Power supply unit (PSU) form factor: SFX-L, 80 PLUS certification: 80 PLUS Platinum. Product colour: Black, Silver, Cooling type: Active, Fan diameter: 12 cm. Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	1200 W	ATX power connector (20+4 pin)	✓
Peak power	1200 W	Cabling type	Fully-Modular
AC input voltage *	100 - 240 V	<b>Performance</b>	
Power Factor Correction (PFC) type	Active	80 PLUS certification *	80 PLUS Platinum
Combined power (+3.3V)	110 W	Purpose *	PC
Combined power (+12V)	1200 W	Power supply unit (PSU) form factor *	SFX-L
Combined power (+5V)	110 W	ATX version	3.1
Combined power (-12V)	9.6 W	Bearing technology	Ball bearing
Combined power (+5Vsb)	15 W	<b>Design</b>	
Max output current (+3.3V)	20 A	Product colour	Black, Silver
Max output current (+12V)	100 A	Cooling type	Active
Max output current (+5V)	20 A	Fan diameter	12 cm
Max output current (-12V)	0.8 A	Number of fans	1 fan(s)
Max output current (+5Vsb)	3 A	Illumination	✓
Power protection features	Over power, Over voltage, Overcharge, Overheating, Short circuit, Under voltage	On/off switch	✓
Ports & interfaces		Packaging content	
Motherboard power connector *	20+4 pin ATX	Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
Motherboard power cable length	45 cm	<b>Certificates</b>	
Number of SATA power connectors	6	Compliance certificates	RoHS
SATA power cable length	100,200,300 mm	<b>Weight &amp; dimensions</b>	
Peripheral (Molex) power connectors (4-pin) *	4	Width	125 mm
Peripheral (Molex) power cable length	100,300 mm	Depth	125 mm
PCI Express power connectors (8-pin)	4	Height	63.5 mm
PCI Express power connectors (16-pin)	2	Weight	2.15 kg

Ports & interfaces		Packaging data	
CPU power connector (4+4 pin)	✓	Manual	✓
CPU power cable length	55 cm	Package width	285 mm
		Package depth	190 mm
		Package height	100 mm
		Package weight	2.84 kg
		Package type	Box
		Technical details	
		Sustainability compliance	✓
		Logistics data	
		Warranty period	10 year(s)



4711081721574

### **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.