



Lenovo 4XB7A17098 internal solid state drive 3.5" 960 GB Serial ATA III TLC 3D NAND

Brand : Lenovo

Product code: 4XB7A17098

Product name : 4XB7A17098




3.5" 5300 960GB Mainstream SATA 6Gb Hot Swap

Lenovo 4XB7A17098 internal solid state drive 3.5" 960 GB Serial ATA III TLC 3D NAND:

The ThinkSystem 5300 Mainstream SATA 6Gb solid-state drives (SSDs) use Micron NAND flash memory technology with a SATA 6Gbps interface to provide an affordable solution for mixed read/write workloads.

This product guide provides essential presales information to understand the 5300 Mainstream SSD offerings, their key features and specifications, components and options, and configuration guidelines. This guide is intended for technical specialists, sales specialists, sales engineers, IT architects, and other IT professionals who want to learn more about the SSDs and consider their use in IT solutions. Lenovo 4XB7A17098. SSD capacity: 960 GB, SSD form factor: 3.5", Component for: Server/workstation

Features		Features	
Security algorithms	256-bit AES	Certification	Micron Green Standard Built with sulfur resistant resistors CE (Europe): EN 55032 Class B, RoHS FCC: CFR Title 47, Part 15 Class B UL: UL-60950-1, 2nd Edition BSMI (Taiwan): approval to CNS 13438 RCM (Australia, New Zealand): AS/NZS CISPR32 Class B KCC RRL (Korea): approval to KN 32 Class B, KN 35 Class B W.E.E.E.: Compliance with EU WEEE directive 2002/96/EC. TUV (Germany): approval to IEC60950/EN60950 VCCI (Japan): 2015-04 Class B IC (Canada): CISPR32 Class B: Canadian ICES-003:2016
SSD form factor *	3.5"		
SSD capacity *	960 GB		
Interface *	Serial ATA III		
Memory type *	TLC 3D NAND		
NVMe *	✗		
Component for *	Server/workstation		
Hardware encryption *	✗		
Random read (4KB)	95000 IOPS		
Random write (4KB)	75000 IOPS		
Read latency	175 μs	Power	
Write latency	100 μs		
S.M.A.R.T. support	✓	Power consumption (read)	2.8 W
Hot-swap	✓	Power consumption (write)	3.4 W
Uncorrectable Bit Error Rate (UBER)	< 1 per 10^17 bits read	Operational conditions	
Mean time between failures (MTBF)	3000000 h		
		Weight & dimensions	
		Width	70 mm
		Depth	100 mm
		Height	7 mm
		Weight	70 g



0889488511174



889488511174

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-JUN-2024. Prints or copies of Information are only valid on the printed Publication date