

ATGBICS 1442200G1 AdTran Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m)

Brand : ATGBICS

Product code: 1442200G1-C

Product name : 1442200G1 AdTran Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m)



1442200G1 AdTran Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m)

ATGBICS 1442200G1 AdTran Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m):

ATGBICS 1442200G1 1000BASE-T SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. AdTran 100BASE-T SFP modules support 10/100 auto negotiation and auto MDI/MDIX. Our product meets the specification of AdTran 1442200G1= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS 1442200G1 AdTran Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m). SFP transceiver type: Copper, Maximum data transfer rate: 100 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box



Performance		Power	
SFP transceiver type *	Copper	Input voltage	3.3 V
Maximum data transfer rate *	100 Mbit/s	Maximum voltage	4 V
Interface type *	SFP	Power consumption (typical)	1.3 W
Single-mode fiber (SMF) supported	✗	Operational conditions	
Multi-mode fiber (MMF) supported	✗	Maximum operating temperature	70 °C
SFP transceiver standard	TX	Operating temperature (T-T)	0 - 70 °C
Maximum transfer distance	100 m	Storage temperature (T-T)	-40 - 85 °C
Ethernet LAN	✓	Operating relative humidity (H-H)	5 - 85%
Ethernet interface type	Fast Ethernet	Storage relative humidity (H-H)	5 - 85%
Copper ethernet cabling technology	100BASE	Weight & dimensions	
Auto MDI/MDI-X	✓	Width	13.4 mm
Digital Diagnostics Monitoring (DDM)	✗	Depth	56.5 mm
Features		Height	8.5 mm
Product colour	Silver	Weight	20 g
Housing material	Metal	Packaging data	
Plug and Play	✓	Number of products included	1 pc(s)
Hot-Plug support	✓	Package type	Box
Hot-swap	✓	Technical details	
Easy to install	✓	Sustainability compliance	✓
Country of origin	United Kingdom	Sustainability certificates	RoHS
Brand compatibility	Adtran	Doesn't contain	Lead
Certification	CE, FCC, RoHS	Compliance certificates	RoHS



5056468701510

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-JUN-2024. Prints or copies of Information are only valid on the printed Publication date