ATGBICS DEM-315GT D-Link Compatible Transceiver SFP 1000Base-ZX (1550nm SMF 80km LC DOM)

Brand : ATGBICS

Product code: DEM-315GT-C



Product name : DEM-315GT D-Link Compatible Transceiver SFP 1000Base-ZX (1550nm SMF 80km LC DOM)

DEM-315GT D-Link Compatible Transceiver SFP 1000Base-ZX (1550nm SMF 80km LC DOM)

ATGBICS DEM-315GT D-Link Compatible Transceiver SFP 1000Base-ZX (1550nm SMF 80km LC DOM):

ATGBICS D-Link compatible DEM-315GT SFP 1000Base-ZX form factor network transceiver supports a distance of up to 80km over single-mode fibre (SMF) using a wavelength of 1550nm via an LC Duplex connector. This product operates within a commercial temperature range. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of D-Link DEM-315GT and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.

Performance		Power	
SFP transceiver type *	Fiber optic	Maximum voltage	3.5 V
Maximum data transfer rate *	1000 Mbit/s	Power consumption (typical)	0.8 W
Interface type *	SFP	Certificates	
Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector	× LC	Compliance certificates	TÜV mark, UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
SFP transceiver standard	ZX	Certification	CE, FCC, RoHS, REACH
Maximum transfer distance	80000 m	Sustainability	
Wavelength	1550 nm	Sustainability compliance	 Image: A set of the set of the
Ethernet LAN	1	Doesn't contain	Lead
Ethernet interface type	Gigabit Ethernet	Operational conditions	
Fiber ethernet cabling technology Digital Diagnostics Monitoring (DDM)	1000BASE	Minimum operating temperature Maximum operating temperature	0 °C 70 °C
Wavelength-division multiplexing (WDM)	×	Operating temperature (T-T) Storage temperature (T-T)	0 - 70 °C -40 - 85 °C
Features		Operating relative humidity (H-H)	5 - 95%
Product colour	Silver	Storage relative humidity (H-H)	5 - 95%
Housing material	Metal	Weight & dimensions	
Plug and Play	 Image: A start of the start of	Width	13.4 mm
Hot-Plug support	✓	Depth	56.5 mm
Hot-swap	1	Height	8.5 mm
Easy to install	1	Weight	20 g
Brand compatibility	D-Link	Packaging content	
Power		Quantity per pack	1 pc(s)
Input voltage	3.3 V	Packaging data	
		Package type	Box
		Logistics data	

Country of origin

United Kingdom

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.