ATGBICS J4860D HPE Compatible Transceiver SFP 1000Base-ZX (1550nm, SMF, 80km, LC, DOM)

Brand : ATGBICS Product code: J4860D-C

Product name : J4860D HPE Compatible Transceiver SFP

1000Base-ZX (1550nm, SMF, 80km, LC, DOM)



J4860D HPE Compatible Transceiver SFP 1000Base-ZX (1550nm, SMF, 80km, LC, DOM)

ATGBICS J4860D HPE Compatible Transceiver SFP 1000Base-ZX (1550nm, SMF, 80km, LC, DOM):

ATGBICS J4860D 1000Base-ZX supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1550nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of HPE J4860D= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic Maximum data transfer rate * 1000 Mbit/s Interface type * SFP Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring	1000 Mbit/s SFP	Certification	CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 0.8 W
		Operational conditions	
	1550 nm	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 95% 5 - 95%
(DDM)	•	Weight & dimensions	
Wavelength-division multiplexing (WDM)	×	Width	13.4 mm
Features		Depth	56.5 mm
Product colour Housing material	Silver Metal	Height Weight	8.5 mm 20 g
Plug and Play	√	Packaging data	
lot-Plug support vlot-swap v	*	Number of products included Package type	1 pc(s) Box
Easy to install	✓	Technical details	
Country of origin United Kin Brand compatibility HP	United Kingdom HP	Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468707024

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.