

ATGBICS QFX-SFP-1GE-T Juniper Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

Brand : ATGBICS

Product code: QFX-SFP-1GE-T-C

Product name : QFX-SFP-1GE-T Juniper Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)



QFX-SFP-1GE-T Juniper Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

ATGBICS QFX-SFP-1GE-T Juniper Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m):

ATGBICS QFX-SFP-1GE-T SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Juniper 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product meets the specification of Juniper QFX-SFP-1GE-T= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS QFX-SFP-1GE-T Juniper Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m). SFP transceiver type: Copper, Maximum data transfer rate: 1000 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Brand compatibility: Juniper. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Compliance certificates: RoHS, Certification: CE, FCC, RoHS. Doesn't contain: Lead



Performance		Power	
SFP transceiver type *	Copper	Power consumption (typical)	1.3 W
Maximum data transfer rate *	1000 Mbit/s	Certificates	
Interface type *	SFP	Compliance certificates	RoHS
Single-mode fiber (SMF) supported	✗	Certification	CE, FCC, RoHS
Multi-mode fiber (MMF) supported	✗	Sustainability	
SFP transceiver standard	TX	Sustainability compliance	✓
Maximum transfer distance	100 m	Doesn't contain	Lead
Ethernet LAN	✓	Operational conditions	
Ethernet interface type	Gigabit Ethernet	Maximum operating temperature	70 °C
Copper ethernet cabling technology	10BASE, 100BASE, 1000BASE	Operating temperature (T-T)	0 - 70 °C
Auto MDI/MDI-X	✓	Storage temperature (T-T)	-40 - 85 °C
Digital Diagnostics Monitoring (DDM)	✗	Operating relative humidity (H-H)	5 - 85%
Features		Storage relative humidity (H-H)	5 - 85%
Product colour	Silver	Weight & dimensions	
Housing material	Metal	Width	13.4 mm
Plug and Play	✓	Depth	56.5 mm
Hot-Plug support	✓	Height	8.5 mm
Hot-swap	✓	Weight	20 g
Easy to install	✓	Packaging content	
Brand compatibility	Juniper	Quantity per pack	1 pc(s)
Power		Packaging data	
Input voltage	3.3 V	Package type	Box
Maximum voltage	4 V	Logistics data	
		Country of origin	United Kingdom



5056468700902

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-OCT-2024. Prints or copies of Information are only valid on the printed Publication date