ATGBICS QSFP-100G-LR4-AR Arista Compatible Transceiver QSFP28 100GBase-LR4 (1310nm, SMF, 10km, LC, DOM)

Brand : ATGBICS

Performance

Interface type *

Wavelength

(DDM) Features Product colour

Ethernet LAN

Housing material

Hot-Plug support

Plug and Play

Easy to install

Certification

Country of origin

Brand compatibility

Hot-swap

SFP transceiver type * Maximum data transfer rate *

Fiber optic connector SFP transceiver standard

Maximum transfer distance

Digital Diagnostics Monitoring

Ethernet interface type

Single-mode fiber (SMF) supported

Multi-mode fiber (MMF) supported

Product code: QSFP-100G-LR4-AR-C

Product name : QSFP-100G-LR4-AR Arista Compatible Transceiver QSFP28 100GBase-LR4 (1310nm, SMF, 10km, LC, DOM)

QSFP-100G-LR4-AR Arista Compatible Transceiver QSFP28 100GBase-LR4 (1310nm, SMF, 10km, LC, DOM)

ATGBICS QSFP-100G-LR4-AR Arista Compatible Transceiver QSFP28 100GBase-LR4 (1310nm, SMF, 10km, LC, DOM):

Fiber optic

OSFP28

1

× LC

LR4 10000 m

1

1

Silver

Metal

1

1

∢

1

United Kingdom

Arista Networks

CE, FCC, RoHS

1310 nm


100 Gigabit Ethernet

100000 Mbit/s

ATGBICS QSFP-100G-LR4-AR 100GBase-LR4 QSFP28 supports a distance of up to 10Km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of QSFP-100G-LR4-AR= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

| Power | |
|---|---|
| Input voltage Maximum voltage Power consumption (typical) | 3.3 V 3.5 V 4 W |
| Operational conditions | |
| Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95% |
| Weight & dimensions | |
| Width Depth Height Weight | 13.5 mm 72.4 mm 18.4 mm 100 g |
| Packaging data | |
| Number of products included Package type | l pc(s) Box |
| Technical details | |
| Sustainability compliance Doesn't contain Compliance certificates | ✔ Lead RoHS |





5056468716910

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.