

ATGBICS RDH901002/1 Ericsson Compatible Transceiver SFP
10/100/1000Base-T (RJ45 Copper 100m)



Brand : ATGBICS

Product code: RDH901002/1-C

Product name : RDH901002/1 Ericsson Compatible
Transceiver SFP 10/100/1000Base-T (RJ45 Copper 100m)

RDH901002/1 Ericsson Compatible Transceiver SFP 10/100/1000Base-T (RJ45 Copper 100m)

ATGBICS RDH901002/1 Ericsson Compatible Transceiver SFP 10/100/1000Base-T (RJ45 Copper 100m):

ATGBICS Ericsson compatible RDH901002/1 SFP 10/100/1000Base-T form factor network transceiver supports a distance of up to 100m over a copper connection via an RJ45 connector. This product operates within a commercial temperature range. Our product meets the specification of Ericsson RDH901002/1 and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.

Performance		Certificates	
SFP transceiver type *	Copper	Compliance certificates	TÜV mark, UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
Maximum data transfer rate *	1000 Mbit/s		
Interface type *	SFP		
Fiber optic connector	RJ-45	Certification	CE, FCC, RoHS, REACH
SFP transceiver standard	TX	Sustainability	
Maximum transfer distance	100 m	Sustainability compliance	✓
Ethernet LAN	✓	Doesn't contain	Lead
Ethernet interface type	Gigabit Ethernet	Operational conditions	
Copper ethernet cabling technology	1000BASE	Minimum operating temperature	0 °C
Auto MDI/MDI-X	✓	Maximum operating temperature	70 °C
Digital Diagnostics Monitoring (DDM)	✗	Operating temperature (T-T)	0 - 70 °C
Features		Storage temperature (T-T)	-40 - 85 °C
Product colour	Silver	Operating relative humidity (H-H)	5 - 85%
Housing material	Metal	Storage relative humidity (H-H)	5 - 85%
Plug and Play	✓	Weight & dimensions	
Hot-Plug support	✓	Width	13.4 mm
Hot-swap	✓	Depth	56.5 mm
Easy to install	✓	Height	8.5 mm
Brand compatibility	Ericsson	Weight	20 g
Power		Packaging content	
Input voltage	3.3 V	Quantity per pack	1 pc(s)
Maximum voltage	4 V	Packaging data	
Power consumption (typical)	1.3 W	Package type	Box
Logistics data			
		Country of origin	United Kingdom

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.