

ATGBICS XFP-1XGE-LR Juniper Compatible Transceiver XFP 10GBase (1310nm SMF 10km LC DOM)



Brand : ATGBICS

Product code: XFP-1XGE-LR-C

Product name : XFP-1XGE-LR Juniper Compatible
Transceiver XFP 10GBase (1310nm SMF 10km LC DOM)

XFP-1XGE-LR Juniper Compatible Transceiver XFP 10GBase (1310nm SMF 10km LC DOM)

ATGBICS XFP-1XGE-LR Juniper Compatible Transceiver XFP 10GBase (1310nm SMF 10km LC DOM):

ATGBICS Juniper compatible XFP-1XGE-LR XFP 10GBase form factor network transceiver supports a distance of up to 10km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC Duplex connector. This product operates within a commercial temperature range. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Juniper XFP-1XGE-LR and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.

Performance		Power	
SFP transceiver type *	Fiber optic	Maximum voltage	3.5 V
Maximum data transfer rate *	10000 Mbit/s	Power consumption (typical)	1.5 W
Interface type *	XFP	Certificates	
Single-mode fiber (SMF) supported	✓	Compliance certificates	UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
Multi-mode fiber (MMF) supported	✗	Certification	CE, FCC, RoHS, REACH
Fiber optic connector	LC	Sustainability	
SFP transceiver standard	LR	Sustainability compliance	✓
Maximum transfer distance	10000 m	Doesn't contain	Lead
Wavelength	1310 nm	Operational conditions	
Ethernet LAN	✓	Minimum operating temperature	0 °C
Ethernet interface type	10 Gigabit Ethernet	Maximum operating temperature	70 °C
Fiber ethernet cabling technology	10GBASE	Operating temperature (T-T)	0 - 70 °C
Digital Diagnostics Monitoring (DDM)	✓	Storage temperature (T-T)	-40 - 85 °C
Wavelength-division multiplexing (WDM)	✗	Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)			0 - 95%
Features		Weight & dimensions	
Product colour	Silver	Width	18.5 mm
Housing material	Metal	Depth	78 mm
Plug and Play	✓	Height	8.5 mm
Hot-Plug support	✓	Weight	36 g
Hot-swap	✓	Packaging content	
Easy to install	✓	Quantity per pack	1 pc(s)
Brand compatibility	Juniper	Packaging data	
Power		Package type	Box
Input voltage	3.3 V	Logistics data	
		Country of origin	Taiwan, China

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-MAY-2025. Prints or copies of Information are only valid on the printed Publication date