## ATGBICS SC-ST OS2 Fibre Patch Cable Singlemode Simplex Yellow 7m

Product code: CAB-OS2-SC-ST-7M-S

Brand : ATGBICS

**Product name :** SC-ST OS2 Fibre Patch Cable Singlemode Simplex Yellow 7m

SC-ST OS2 Fibre Patch Cable Singlemode Simplex Yellow 7m

ATGBICS SC-ST OS2 Fibre Patch Cable Singlemode Simplex Yellow 7m:

7 m 0S2

0.2 dB

This product is high quality SC-ST (male to male) Fibre Patch Cable. Simplex Fibre is most often used for applications that only require one-way data transfer. This is a single mode cable which renders it very stable as they are only thick enough to carry one wave of light. This eliminates distortion caused by overlapping light signals. The OS2 cable is used for high speed data transfer. The OS2 cable has a core size of just 9 microns and the diameter of the outer cladding is 125 microns. OS2 is backward compatible with OS7

ATGBICS SC-ST OS2 Fibre Patch Cable Singlemode Simplex Yellow 7m. Cable length: 7 m, Fibre optic type: OS2, Connector 1: SC, Connector 2: ST, Core diameter: 9  $\mu$ m

Cable length *
Fibre optic type
Cable shape
Fastening type
Connector 1 *
Connector 2 *
Connector 1 gender *
Connector 2 gender *
Connector polish type
Product colour *
Full duplex
Core diameter
Cladding diameter
Fiber mode structure
Wavelengths supported
Ethernet interface type
Insertion loss

Round
Push-pull
SC
ST
Male
Male
UPC
Yellow
×
9 μm
125 µm
Single-mode
1310,1550 nm
Gigabit Ethernet, 10 Gigabit Ethernet

Features	
Return loss Jacket material * Plug and Play	50 dB Low smoke zero halogen (LSZH) ✔
Sustainability	
Doesn't contain	Halogen
Certificates	
Compliance certificates Certification	REACH, RoHS, UKCA, CE CE, FCC, RoHS, REACH
Operational conditions	
Operating temperature (T-T) Storage temperature (T-T)	-10 - 70 °C -40 - 85 °C
Storage temperature (T-T)	
Storage temperature (T-T) Weight & dimensions	-40 - 85 °C
Storage temperature (T-T) Weight & dimensions Cable diameter	-40 - 85 °C
Storage temperature (T-T)         Weight & dimensions         Cable diameter         Packaging content	-40 - 85 °C 2 mm



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.