## ATGBICS MPO Female-4 LC Duplex 8 Fibres OS2 9/125 Singlemode Breakout Cable, Type B, LSZH 2.0, 2m

Brand: ATGBICS Product code: BOC-8MPOF-4LCOS2-2M

**Product name :** ATGBICS MPO Female-4 LC Duplex 8 Fibres OS2 9/125 Singlemode Breakout Cable, Type B,

LSZH 2.0, 2m

ATGBICS

ATGBICS MPO Female-4 LC Duplex 8 Fibres OS2 9/125 Singlemode Breakout Cable, Type B, LSZH 3.0, 2m

ATGBICS MPO Female-4 LC Duplex 8 Fibres OS2 9/125 Singlemode Breakout Cable, Type B, LSZH 2.0, 2m:

This product is high quality MPO Breakout Cable, designed for data centre high-density fibre patching. They are space saving and ease cable management problems. This is an OS2 8-fibre cable over singlemode, optimally used for 40G QSFP+ PLR4 to 10G SFP+ LR. It enables one QSFP+ transceiver to be connected to either 4 x SFP+ transceivers or 4 LC ports within patch panels or MPO cassettes. QSFP+ transceivers which support 40GBASE-PLR4 have ports with a male connection. These require an MPO to LC breakout cable with a female MPO connector such as this product. The MPO connection interface has been defined within the IEC-61754-7 international standards. Our products are rigorously tested and we proudly offer a compatibility guarantee and lifetime warranty.



Features		Features	
Cable length * Fibre optic type Connector 1 * Connector 2 * Connector 1 gender *	re optic type  onector 1 *  onector 2 *  onector 1 gender *  oduct colour *  I duplex  re diameter  dding diameter  er mode structure  velengths supported  OS2  MPO  4x LC  Female  Yellow  ✓  Yellow  ✓  I duplex  ✓  Single-mode  1310,1550 nm  10 Gigabit Ethernet 40 Gigabit	Insertion loss Return loss Jacket material * Polarity Country of origin	0.5 dB 50 dB Low smoke zero halogen (LSZH) B China
Product colour * Full duplex Core diameter Cladding diameter		Technical details  Doesn't contain  Compliance certificates  Operational conditions	Halogen RoHS
Wavelengths supported Ethernet interface type		Operational conditions Operating temperature (T-T) Storage temperature (T-T) Packaging data Quantity per pack	-10 - 70 °C -40 - 85 °C 1 pc(s)



5056468745071

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.