## ATGBICS MC2309130-001 Mellanox Compatible Direct Attach Copper Twinax Cable, 40G QSFP+ to 10G SFP+ (1m, Passive)

Brand: ATGBICS Product code: MC2309130-001-C

**Product name :** MC2309130-001 Mellanox Compatible Direct Attach Copper Twinax Cable, 40G QSFP+ to 10G SFP+ (1m, Passive)

MC2309130-001 Mellanox Compatible Direct Attach Copper Twinax Cable, 40G QSFP+ to 10G SFP+ (1m, Passive)

ATGBICS MC2309130-001 Mellanox Compatible Direct Attach Copper Twinax Cable, 40G QSFP+ to 10G SFP+ (1m, Passive):

ATGBICS MC2309130-001 compatible 1 x 40GBase QSFP+ to 1 x 10BGase SFP+ direct attach cable operates over passive copper with a cable length of 1m. It is suitable for short reach connectivity between devices with a QSFP port on one end and an SFP+ port on the other end. This QSFP+ to SFP+ DAC significantly reduces power consumption and extends the connectivity opportunities of the network. Our product meets the specification of Mellanox MC2309130-001= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; QSFP MSA SFF-8436 and SFP+ MSA SFF-8431

ATGBICS MC2309130-001 Mellanox Compatible Direct Attach Copper Twinax Cable, 40G QSFP+ to 10G SFP+ (1m, Passive). Cable length: 1 m, Connector 1: QSFP+, Connector 2: SFP+







Features		Features	
Cable length * Connector 1 *	nector 1 * QSFP+ nector 2 * SFP+ nector 1 gender * Male nector 2 gender * Male duct colour * Black ernet interface type a transfer rate tet material * Polyvinyl chloride (PVC) ductor material nd compatibility  QSFP+ QSFP+ Nale Nale Nale Nale Nale Nale Nale Nale	Country of origin Certification	United Kingdom CE, FCC, RoHS
Connector 2 * Connector 1 gender *		Technical details	
Connector 2 gender * Product colour *		Sustainability compliance Doesn't contain Compliance certificates	✓ Lead RoHS
Ethernet interface type		Operational conditions	
Data transfer rate  Jacket material *		Operating temperature (T-T) Storage temperature (T-T)	0 - 70 °C -40 - 80 °C
Conductor material Brand compatibility		Packaging data	
Plug and Play		Quantity per pack	1 pc(s)
		Other features	
		Networking standards	IEEE 802.3ae



5056468720986

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.