ATGBICS TRX100090/TC Transmode Compatible Transceiver DWDM XFP 10GBase OC-192/STM-64/10G SONET ZR Tunable (SMF, 80km, DOM)

Brand : ATGBICS Product code: TRX100090/TC-C



Product name : TRX100090/TC Transmode Compatible Transceiver DWDM XFP 10GBase OC-192/STM-64/10G SONET ZR Tunable (SMF, 80km, DOM)

TRX100090/TC Transmode Compatible Transceiver DWDM XFP 10GBase OC-192/STM-64/10G SONET ZR Tunable (SMF, 80km, DOM)

ATGBICS TRX100090/TC Transmode Compatible Transceiver DWDM XFP 10GBase OC-192/STM-64/10G SONET ZR Tunable (SMF, 80km, DOM). SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: XFP. Product colour: Silver, Housing material: Metal, Country of origin: China. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 1 W. Width: 18.5 mm, Depth: 78 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box



| Performance | | Power | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
| Interface type * XFP Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector Maximum transfer distance Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring | 10000 Mbit/s | Input voltage Maximum voltage Power consumption (typical) | 3.3 V 3.5 V 1 W |
| | X LC | Operational conditions Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95% |
| (DDM) Features | • | Weight & dimensions Width | 18.5 mm |
| Product colour Silver Housing material Metal Plug and Play | | Depth Height Weight | 78 mm 8.5 mm 36 g |
| Hot-Plug support | ✓ ✓ China Transmode CE, FCC, RoHS | Packaging data | |
| Hot-swap Easy to install | | Number of products included Package type | 1 pc(s) Box |
| Country of origin Brand compatibility | | Technical details | |
| Certification | | Sustainability compliance Sustainability certificates Doesn't contain | √ RoHS Lead |



5056468746511

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.