ATGBICS QSFP-4SFP25G-CU2M Cisco Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to 4x25G SFP28 (2m, Passive)

Brand: ATGBICS Product code: QSFP-4SFP25G-CU2M-C

Product name : QSFP-4SFP25G-CU2M Cisco Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to

4x25G SFP28 (2m, Passive)

QSFP-4SFP25G-CU2M Cisco Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to 4x25G SFP28 (2m, Passive)

ATGBICS QSFP-4SFP25G-CU2M Cisco Compatible Direct Attach Copper Breakout Cable 100G QSFP28 to 4x25G SFP28 (2m, Passive):

ATGBICS QSFP-4SFP25G-CU2M compatible 100GBase QSFP28 to 4x25G SFP28 direct attach breakout cable operates over passive copper with a cable length of 2m. It is suitable for very short distances and provides a cost-efficient way to connect hardware within close proximity racks. This breakout cable connects to 1 x 100G QSFP+ port of a switch on one end and to 4 x 25G SFP+ ports of a switch on the other end. Our product meets the specification of Cisco QSFP-4SFP25G-CU2M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; IEEE802.3bj, InfiniBand EDR, MSA SFF-8665 & SFF-8402.







Features		Features	
Cable length *	X QSFP28	Certification	CE, FCC, RoHS
Connector 1 *		Technical details	
Connector 2 * SFP28 Connector 1 gender * Male Connector 2 gender * Male Product colour * Black	Sustainability compliance Sustainability certificates Doesn't contain	√ RoHS Lead	
Ethernet interface type	hernet interface type ata transfer rate cket material * polyvinyl chloride (PVC) conductor material g and Play 100 Gigabit Ethernet 100000 Mbit/s Polyvinyl chloride (PVC) Copper	Operational conditions	
Data transfer rate Jacket material *		Operating temperature (T-T) Storage temperature (T-T)	0 - 70 °C -40 - 80 °C
Conductor material		Packaging data	
Plug and Play Country of origin		Quantity per pack	1 pc(s)
		Other features	
		Networking standards	IEEE 802.3bj



5056468724816

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.