## ATGBICS SFP-10GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (1m, Passive)

Brand : ATGBICS Product code: SFP-10GE-DAC-1M-C

**Product name :** SFP-10GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (1m, Passive)

SFP-10GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (1m, Passive)

ATGBICS SFP-10GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (1m, Passive):

ATGBICS SFP-10GE-DAC-1M compatible 10GBase-CU SFP+ to SFP+ direct attach cable operates over passive copper with a cable length of 1m. It is suitable for short reach connection between two SFP+ ports in 10G interconnecting networking applications. Our product meets the specification of Juniper SFP-10GE-DAC-1M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 1x InfiniBand QDR, DDR, SDR, 10G Gigabit Ethernet, Fibre Channel, MSA SPF+ SFF-8431, SFF-8432, and SFF-8472 compliant.

ATGBICS SFP-10GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (1m, Passive). Cable length: 1 m, Connector 1: SFP+, Connector 2: SFP+







Features		Features	
Cable length *	1 m	Certification	CE, FCC, RoHS
Connector 1 *	SFP+  Sonnector 1 gender * Male  Sonnector 2 gender * Male  roduct colour * Black  thernet interface type 10 Gigabit Ethernet  stata transfer rate 10000 Mbit/s  secket material * Polyvinyl chloride (PVC)  Sonductor material Copper  lug and Play	Technical details	
Connector 1 gender * Connector 2 gender *		Sustainability compliance Doesn't contain Compliance certificates	✓ Lead RoHS
Ethernet interface type		Operational conditions	
Data transfer rate  Jacket material *		Operating temperature (T-T) Storage temperature (T-T)	0 - 70 °C -40 - 80 °C
Conductor material		Packaging data	
Plug and Play Country of origin		Quantity per pack	1 pc(s)
		Other features	
		Networking standards	IEEE 802.3ae



5056468720962

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.