## ATGBICS SP-CABLE-ADASFP+ Fortinet Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (10m, Active)

**Brand:** ATGBICS Product code: SP-CABLE-ADASFP+-C

**Product name:** SP-CABLE-ADASFP+ Fortinet Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (10m,

Active)

SP-CABLE-ADASFP+ Fortinet Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (10m, Active)

ATGBICS SP-CABLE-ADASFP+ Fortinet Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (10m, Active):

ATGBICS SP-CABLE-ADASFP+ compatible 10GBase-CU SFP+ to SFP+ direct attach cable operates over active copper with a cable length of 10m. It is suitable for short reach connection between two SFP+ ports in 10G interconnecting networking applications. Our product meets the specification of Fortinet SP-CABLE-ADASFP+= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 1x InfiniBand QDR, DDR, SDR, 10G Gigabit Ethernet, Fibre Channel, MSA SPF+ SFF-8431, SFF-8432, and SFF-8472 compliant.

ATGBICS SP-CABLE-ADASFP+ Fortinet Compatible Direct Attach Copper Twinax Cable 10G SFP+ Cu (10m, Active). Cable length: 10 m, Connector 1: SFP+, Connector 2: SFP+







Features		Features	
Cable length *       10 m         Connector 1 *       SFP+         Connector 2 *       SFP+         Connector 1 gender *       Male         Connector 2 gender *       Male         Product colour *       Black	SFP+ SFP+ Male	Country of origin Certification  Technical details  Sustainability compliance  Doesn't contain	United Kingdom CE, FCC, RoHS ✓ Lead
Ethernet interface type Data transfer rate Jacket material *	ernet interface type 10 Gigabit Ethernet ta transfer rate 10000 Mbit/s ket material * Polyvinyl chloride (PVC) nductor material Copper and compatibility Fortinet	Compliance certificates  Operational conditions  Operating temperature (T-T)	RoHS 0 - 70 °C
Conductor material Brand compatibility Plug and Play		Storage temperature (T-T)  Packaging data  Quantity per pack	-40 - 80 °C 1 pc(s)
		Other features Networking standards	IEEE 802.3ae



5056468723123

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.