



Dahua Technology DHI-XVR5116H-4KL videgrabadora digital Negro



Marca : Dahua Technology

Código del producto: DHI-XVR5116H-4KL

Nombre del producto : DHI-XVR5116H-4KL

Dahua Technology DHI-XVR5116H-4KL. Color del producto: Negro, Formatos de compresión de video: H.264, H.264+, Resoluciones de reproducción soportadas: 3840 x 2160 2560x1440 1920x1080 1280x1024 1280x720 1024x768. Tipo de interfaz ethernet: Gigabit Ethernet, Protocolos de red compatibles: HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm.... Interfaz del HDD: SATA, Capacidad máxima del HDD: 8 TB. Consumo energético: 15 W. Dimensiones (Ancho x Profundidad x Altura): 325 x 255 x 55 mm, Peso: 1.5 kg

Desempeño		Red	
Formatos de compresión de video	H.264, H.264+	Tipo de interfaz ethernet	Gigabit Ethernet
Resoluciones de reproducción soportadas	3840 x 2160 2560x1440 1920x1080 1280x1024 1280x720 1024x768	Puertos Ethernet LAN (RJ-45)	1
Color del producto *	Negro	Protocolos de red compatibles	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search
Modo de reproducción	Rápido, Next, Pausa, Play, Anterior, Repetir, Barajar, Lento, Alto, Acercar	Disco duro	
Sistema operativo instalado	LINUX incrustado	Número de HDDs soportados	1
Función de pausa	✓	Interfaz del HDD	SATA
Velocidad máxima de cuadro	30 fps	Capacidad máxima del HDD	8 TB
Certificación	FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 UL: UL 60950-1	Procesador	
		Procesador incorporado	✓
		Control de energía	
		Consumo energético	15 W
Puertos e Interfaces		Peso y dimensiones	
puertos de entrada BNC	16	Dimensiones (Ancho x Profundidad x Altura)	325 x 255 x 55 mm
Número de puertos HDMI	1	Peso	1.5 kg
Puertos de salida VGA (D-Sub)	1	Exhibición	
Entrada de audio	1	Resolución de la pantalla	3840 x 2160 Pixeles
Salida de audio	1	Rango de cuadros en pantalla	30 fps
Cantidad de puertos USB 2.0	1	Condiciones ambientales	
Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1)	1	Intervalo de temperatura operativa (T-T)	-10 - 55 °C
Puertos RS-485	1	Intervalo de humedad relativa para funcionamiento	0 - 90%
Red		Intervalo de temperatura de almacenaje	-20 - 70 °C
Ethernet	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-AUG-2024. Prints or copies of Information are only valid on the printed Publication date