

Everyday Toner rigenerato™ di Xerox Giallo compatibile con HP 203X (CF542X), High capacity



Marchio : Xerox

Famiglia del prodotto: Everyday

Codice prodotto: 006R03622

Nome del prodotto : Toner rigenerato Everyday™ di Xerox Giallo compatibile con HP 203X (CF542X), High capacity

Toner rigenerato Everyday™ di Xerox Giallo compatibile con HP 203X (CF542X), High capacity

Everyday Toner rigenerato™ di Xerox Giallo compatibile con HP 203X (CF542X), High capacity:

Un impegno di responsabilità ambientale rappresenta l'approccio migliore dal punto di vista commerciale, per il suo impatto positivo sul pianeta, sull'azienda e sulle persone. Il Toner rigenerato Everyday di Xerox produce un'impronta di carbonio minore rispetto a qualsiasi altra cartuccia di toner a singolo utilizzo. Perché non si dovrebbe essere obbligati a scegliere tra fare la propria parte per ridurre l'impatto sull'ambiente e il costo del toner. E la compatibilità con le marche di stampanti più diffuse ti permette di usufruire dell'impareggiabile qualità e impegno ambientale di Xerox indipendentemente dalla stampante che utilizzi.

Everyday Toner rigenerato™ di Giallo compatibile con HP 203X (CF542X), High capacity. Resa in pagine del toner nero: 2500 pagine, Resa in pagine del toner a colori: 2500 pagine, Colori di stampa: Giallo, Quantità per pacco: 1 pz

Caratteristiche		Condizioni ambientali	
Compatibilità *	HP LaserJet MFP M280 HP LaserJet MFP M281 HP LaserJet Pro M254	Range di umidità di funzionamento	30 - 70%
Quantità per pacco *	1 pz	Intervallo di temperatura	0 - 35 °C
Tipo di cartuccia	Resa elevata (XL)	Umidità	35 - 85%
Resa in pagine del toner nero *	2500 pagine	Dimensioni e peso	
Resa in pagine del toner a colori *	2500 pagine	Peso	698 g
Tipo *	Compatibile	Dati su imballaggio	
Colori di stampa *	Giallo	Larghezza imballo	135 mm
Compatibilità marca *	HP	Profondità imballo	345 mm
Tipo di fornitura *	Confezione singola	Altezza imballo	105 mm
In sostituzione alla	HP 203X	Peso dell'imballo	744 g
Codice OEM	CF542X	Tipo di imballo	Scatola
Paese di origine	Paesi Bassi	Altre caratteristiche	
Condizioni ambientali		Certificazione	RoHS, REACH SVHC, CE MARK STMC, ISO 9001:2015, ISO 14001:2015
Intervallo temperatura di funzionamento	17 - 25 °C	Dati logistici	
		Codice del Sistema Armonizzato (SA)	8443,99,1000
		Quantità per cartone principale	15 pz



0095205894998



095205894998

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-OCT-2024. Prints or copies of Information are only valid on the printed Publication date