

ASUS TUF Gaming 850W Gold power supply unit 24-pin ATX ATX Zwart

Merk : ASUS

Artikelcode: 90YE00S2-B0NA00

Productnaam : TUF Gaming 850W Gold

ASUS TUF Gaming 850W Gold. Totaal vermogen: 850 W, AC-ingangsspanning: 100 - 240 V, Gecombineerd vermogen (+3.3V): 130 W. Motherboard power connector: 24-pin ATX, Lengte stroomkabel moederbord: 61 cm, Lengte SATA-stroomkabel: 120,400 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 13,5 cm. Meegeleverde kabels: AC, CPU, PCIe, Peripheral (Molex), SATA




Energie		Poorten & interfaces	
Totaal vermogen *	850 W	Lengte PCI Express-stroomkabel	67,5 cm
AC-ingangsspanning *	100 - 240 V	CPU power connector (4+4 pin)	✓
Gecombineerd vermogen (+3.3V)	130 W	Lengte CPU-stroomkabel	65 cm
Gecombineerd vermogen (+12V)	850 W	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+5V)	130 W	Prestatie	
Gecombineerd vermogen (-12V)	9,6 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen(+5Vsb)	15 W	Bedoeld voor *	PC
Max huidige output (+3.3V)	25 A	Vormfactor van de voeding (PSU) *	ATX
Max huidige output(+12V)	70,8 A	ATX version	3.0
Max huidige output (+5V)	25 A	Design	
Max huidige output (-12V)	0,8 A	Kleur van het product	Zwart
Max huidige output (+5Vsb)	3 A	Type koeling	Actief
Efficiëntie	92 procent	Ventilator diameter	13,5 cm
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Kortsluiting, Onder spanning	Aantal ventilatoren	1 ventilator(en)
Poorten & interfaces		Inhoud van de verpakking	
Motherboard power connector *	24-pin ATX	Meegeleverde kabels	AC, CPU, PCIe, Peripheral (Molex), SATA
Lengte stroomkabel moederbord	61 cm	Gewicht en omvang	
Aantal SATA power connectors	5	Breedte	150 mm
Lengte SATA-stroomkabel	120,400 mm	Diepte	150 mm
Peripheral (Molex) power connectors (4-pin) *	4	Hoogte	86 mm
Lengte stroomkabel randapparaat (Molex)	150,400 mm	Gewicht	2,38 kg
PCI Express power connectors (8-pin)	3	Verpakking	
PCI Express-voedingsconnectoren (16-pins)	1	Breedte verpakking	310 mm
		Diepte verpakking	200 mm
		Hoogte verpakking	108 mm
		Gewicht verpakking	3,07 kg

Verpakking

Type verpakking	Doos
-----------------	------

Technische details

Certificaten van naleving	RoHS
---------------------------	------



4711081786573

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-AUG-2024. Prints or copies of Information are only valid on the printed Publication date