

StarTech.com 3m USB naar Seriële Adapter Kabel, COM Retention, Verwisselbare DB9 Schroeven/Moeren, USB-A naar RS232 DB9 Converter, FTDI IC, ESD Bescherming, Windows/macOS/Linux

Merk : StarTech.com

Artikelcode: 1P10FFC-USB-SERIAL

Productnaam : 3m USB naar Seriële Adapter Kabel, COM Retention, Verwisselbare DB9 Schroeven/Moeren, USB-A naar RS232 DB9 Converter, FTDI IC, ESD Bescherming, Windows/macOS/Linux



StarTech.com 3m USB naar Seriële Adapter Kabel, COM Retention, FTDI IC, DB9 RS232, Verwisselbare DB9 Schroeven/Moeren

StarTech.com 3m USB naar Seriële Adapter Kabel, COM Retention, Verwisselbare DB9 Schroeven/Moeren, USB-A naar RS232 DB9 Converter, FTDI IC, ESD Bescherming, Windows/macOS/Linux:

Voeg een RS232 seriële poort toe aan een laptop of desktop via een beschikbare USB-A poortThe StarTech.com Advantage

StarTech.com 3m USB naar Seriële Adapter Kabel, COM Retention, Verwisselbare DB9 Schroeven/Moeren, USB-A naar RS232 DB9 Converter, FTDI IC, ESD Bescherming, Windows/macOS/Linux. Kleur van het product: Zwart, Snoerlengte: 3 m, Aansluiting 1: USB Type-A. Breedte verpakking: 220 mm, Diepte verpakking: 1 mm, Hoogte verpakking: 200 mm. Breedte: 34 mm, Hoogte: 16 mm, Gewicht: 120 g. (Buitenste) hoofdverpakking breedte: 570 mm, (Buitenste) hoofdverpakking lengte: 355 mm, (Buitenste) hoofdverpakking hoogte: 290 mm



| Kenmerken | | Verpakking | |
|----------------------------|------------------------------|---|----------------|
| Kleur van het product * | Zwart | Breedte verpakking | 220 mm |
| Snoerlengte * | 3 m | Diepte verpakking | 1 mm |
| Aansluiting 1 * | USB Type-A | Hoogte verpakking | 200 mm |
| Aansluiting 2 * | DB-9 | Gewicht verpakking | 130 g |
| Aansluiting 1 type | Mannelijk | Eisen aan de omgeving | |
| Aansluiting 2 type | Mannelijk | Bedrijfstemperatuur (T-T) | -40 - 80 °C |
| Connector 1 vormfactor | Recht | Temperatuur bij opslag | -40 - 80 °C |
| Connector 2 vormfactor | Recht | Relatieve vochtigheid in bedrijf (V-V) | 0 - 95 procent |
| Chipset | FTDI - FT232R | Gewicht en omvang | |
| Baud snelheid | 921,6 Kbit/s | Breedte | 34 mm |
| Data bits | 7, 8 | Hoogte | 16 mm |
| FIFO (First In, First Out) | 256 B | Gewicht | 120 g |
| Parity bit | Even, Mark, Nee, ODD, Ruimte | Logistieke gegevens | |
| Stop bits | 1, 2 | (Buitenste) hoofdverpakking breedte | 570 mm |
| | | (Buitenste) hoofdverpakking lengte | 355 mm |
| | | (Buitenste) hoofdverpakking hoogte | 290 mm |
| | | Hoeveelheid per (buitenste) hoofdverpakking | 100 stuk(s) |

Kenmerken

| | |
|---------------------------------------|---|
| Ondersteunt Windows | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64 |
| Ondersteunt Mac-besturingssysteem | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura |
| Ondersteunt Linux | ✓ |
| Ondersteunde server operating systems | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022 |



0065030898331



065030898331

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-AUG-2024. Prints or copies of Information are only valid on the printed Publication date