



LevelOne FEP-0800W65 netwerk-switch Fast Ethernet (10/100) Power over Ethernet (PoE) Grijs

Merk : LevelOne

Artikelcode: FEP-0800W65

Productnaam : FEP-0800W65




LevelOne FEP-0800W65. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 8. Full duplex. MAC-adrestabel: 1000 entries, Switchingcapaciteit: 1,6 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3u, IEEE 802.3x. Netstekker: DC-in ingang. Power over Ethernet (PoE)



Poorten & interfaces		Power over Ethernet (PoE)	
Aantal basis-switching RJ-45 Ethernet-poorten *	8	Hoeveelheid Power over Ethernet (PoE) ports	8
Type basis-switching RJ-45 Ethernet-poorten *	Fast Ethernet (10/100)	Vermogen per poort Power over Ethernet (PoE)	30 W
Netstekker	DC-in ingang	Totaal Power over Ethernet (PoE)-budget	60 W
Netwerk		Eisen aan de omgeving	
Netwerkstandaard *	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Bedrijfstemperatuur (T-T)	0 - 45 °C
10G support *	✗	Temperatuur bij opslag	-40 - 75 °C
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Full duplex	✓	Luchtvochtigheid bij opslag	10 - 90 procent
Datastroombeheer	✓	Gewicht en omvang	
Auto MDI/MDI-X	✓	Breedte	165 mm
Auto-negotiation	✓	Diepte	99 mm
Data-uitwisseling		Hoogte	41 mm
Switchingcapaciteit *	1,6 Gbit/s	Gewicht	1,4 kg
MAC-adrestabel *	1000 entries	Verpakking	
Store-and-forward	✓	Meegeleverde kabels	AC
Packet forwarding rate (100 Mbps)	148000 pps	Gebruikershandleiding	✓
Packet forwarding rate (10 Mbps)	14880 pps	Inclusief AC-adapter	✓
Design		Type verpakking	Doos
Rack-montage *	✗	Breedte verpakking	371 mm
Kleur van het product	Grijs	Diepte verpakking	230 mm
LED-indicatoren	Activiteit, Power over Ethernet (PoE), Stroom	Hoogte verpakking	82 mm
Aan/uitschakelaar	✓	Gewicht verpakking	1,6 kg
Land van herkomst	Taiwan	Logistieke gegevens	
Certificering	FCC, CE, RoHS	(Buitenste) hoofdverpakking breedte	525 mm
Prestatie		(Buitenste) hoofdverpakking lengte	246 mm
Buffergrootte	64 KB	(Buitenste) hoofdverpakking hoogte	392 mm
Plug and play	✓	Code geharmoniseerd systeem (HS)	85176990
Energie		(Buitenste) hoofdverpakking brutogewicht	10 kg
Stroomverbruik (typisch)	65 W	Hoeveelheid per (buitenste) hoofdverpakking	6 stuk(s)
Stroomspanning bescherming	Overstroom		

Power over Ethernet (PoE)

Power over Ethernet (PoE) * 



4015867199732

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-SEP-2024. Prints or copies of Information are only valid on the printed Publication date