

ASUS X54L-SX012V 笔记本电脑 Intel® Core™ i3 i3-2310M 39.6 cm (15.6") 4 GB DDR3-SDRAM 640 GB Intel® HD Graphics 3000 Windows 7 Home Premium

品牌 : ASUS

型号 : X54L-SX012V

系列 : X54L-SX012V

ASUS X54L-SX012V. 处理器: Intel® Core™ i3, 处理器: i3-2310M, 处理器: 2.1 GHz. 屏幕(英寸): 39.6 cm (15.6"), 分辨率: 1366 x 768 像素. 内存: 4 GB, 内存: DDR3-SDRAM. 硬盘: 640 GB. 显卡: Intel® HD Graphics 3000, 显卡: Intel® HD Graphics 3000. 操作系统: Windows 7 Home Premium. 重量: 2.6 kg



规格		兼容性	
接口 *	接口	SmartCard接口	×
接口		接口	×
屏幕(英寸) *	39.6 cm (15.6")	接口	
分辨率 *	1366 x 768 像素	接口	Intel® HM65 接口
LED 背光	✓	接口	
屏幕比例	16:9	接口	✓
接口		操作系统 *	Windows 7 Home Premium
处理器 *	Intel	接口	
处理器 *	Intel® Core™ i3	接口	
处理器	接口 Intel® Core™ i3接口	Intel® 接口	✓
处理器 *	i3-2310M	Intel® My WiFi 接口	✓
接口	2	Intel® 接口 接口	✓
接口	4	Intel® 接口接口接口	✓
处理器 *	2.1 GHz	Intel® 接口接口	✓
接口	5 GT/秒	Intel® Turbo Boost Technology (接口 接口)	×
接口	3 MB	接口Intel® SpeedStep接口	✓
接口接口	接口接口	Intel® 接口接口接口	✓
接口	BGA 1023	Intel® Clear Video Technology	×
接口	32 nm	接口Intel® 接口接口接口	×
接口接口	64接口	Intel® InTru™ 3D 接口	✓
接口	Intel Core i3-2300 Mobile Series	Intel® Insider™	✓
接口接口codename接口	Sandy Bridge	Intel® Quick Sync Video Technology (接口接口接口)	✓
接口	DMI	Intel® Flex接口接口接口	✓
FSB接口	×	Intel® 接口接口接口接口	×
接口	J1	Intel® 接口接口接口	×
接口接口TDP接口	35 W		
接口接口接口接口	100 °C		
PCI Express 接口接口接口	16		

CPU		CPU	
PCI Express	2.0	Intel®	✓
PCI Express	1x16, 2x8, 1x8+2x4	Intel® VT-x	✓
CPU	21	Intel®	✗
ECC	✗	MID	✗
Memory		Memory	
	4 GB	Intel® 64	✓
	DDR3-SDRAM		✓
	1333 MHz		✓
	1x SO-DIMM		✓
(64-bit)	4 GB		37.5 x 37.5 x rPGA988B); 31 x 24 (BGA1023)
Storage		Storage	
	640 GB	AVX	
	1	SR04S	
	SATA	CPU	1
	✓		✗
	MS, MMC, SD	IMC	32 nm
Graphics		Graphics	
	Intel® HD Graphics 3000	Intel® Identity Protection Technology	1.00
	✓	Intel®	
	✓	Intel® Virtualization Technology (VT-x)	✓
	Intel® HD Graphics	Intel®	✓
	Intel® HD Graphics 3000	Intel®	✓
	650 MHz	Intel® (RST)	✗
	1100 MHz	Intel®	✓
	0x116	ARK ID	52220
Network		Network	
	2		✗
	4G WiMAX		✓
Camera		Camera	
	2		4
	0.3 MP		2600 mAh
			37 Wh
Wireless		Wireless	
Wi-Fi	✓		
	802.11b, 802.11g, Wi-Fi 4 (802.11n)		65 W
LAN	✓	AC	100 - 240 V
	✗		3.42 A
	10/100/1000Base-T(X)		19 V
Connectivity		Connectivity	
		DC - in	✓
Ports		Ports	
USB 2.0	2		
LAN RJ - 45	1		✗
DVI	✗		
VGA D-SUB	1		
	1		378 mm
S / PDIF	✗		253 mm
	✓		3.56 cm
	✗		3.72 cm
	✗		2.6 kg
ExpressCard	✗		
CardBus PCMCIA	✗		✗
			Intel

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.