





# LevelOne GNC-0210 netwerkkaart Intern Ethernet 10000 Mbit/s

**Merk :** LevelOne **Artikelcode:** GNC-0210

**Productnaam :** GNC-0210

LevelOne GNC-0210. Intern. Connectiviteitstechnologie: Bedraad, Hostinterface: PCI Express, Interface: Ethernet. Maximale overdrachtssnelheid van gegevens: 10000 Mbit/s. Kleur van het product: Groen



| Poorten & interfaces                        |                                                                                                                       | Eisen aan de omgeving                           |                                                   |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|---------------------------------------------------|
| Connectiviteitstechnologie *                | Bedraad                                                                                                               | Relatieve vochtigheid in bedrijf (V-V)          | 10 - 90 procent                                   |
| Hostinterface *                             | PCI Express                                                                                                           | Luchtvochtigheid bij opslag                     | 10 - 90 procent                                   |
| Interface *                                 | Ethernet                                                                                                              | <b>Duurzaamheid</b>                             |                                                   |
| Aantal Ethernet LAN (RJ-45)-poorten         | 1                                                                                                                     | Naleving van duurzaamheid                       | ✓                                                 |
| Netwerk                                     |                                                                                                                       | Duurzaamheidscertificaten                       | CE, Federal Communications Commission (FCC), RoHS |
| Maximale overdrachtssnelheid van gegevens * | 10000 Mbit/s                                                                                                          | Gewicht en omvang                               |                                                   |
| Netwerkstandaard *                          | IEEE 1588, IEEE 802.1as, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u | Breedte                                         | 105 mm                                            |
| Ethernet LAN                                | ✓                                                                                                                     | Diepte                                          | 68 mm                                             |
| Ethernet interface type                     | 2.5 Gigabit Ethernet, 5 Gigabit Ethernet, 10 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet                        | Hoogte                                          | 20 mm                                             |
| Ethernet LAN, data-overdrachtsnelheden      | 10,100,1000,2500,5000,10000 Mbit/s                                                                                    | Gewicht                                         | 110 g                                             |
| Bekabelingstechnologie                      | 10GBase-T                                                                                                             | Verpakking                                      |                                                   |
| Wake-on-LAN                                 | ✓                                                                                                                     | Breedte verpakking                              | 183 mm                                            |
| Jumbo Frames ondersteuning                  | ✓                                                                                                                     | Diepte verpakking                               | 152 mm                                            |
| Jumbo frames                                | 16000                                                                                                                 | Hoogte verpakking                               | 30 mm                                             |
| Ondersteunde netwerkprotocollen             | IPv4, IPv6                                                                                                            | Gewicht verpakking                              | 230 g                                             |
| Design                                      |                                                                                                                       | Logistieke gegevens                             |                                                   |
| Component voor *                            | Pc/server                                                                                                             | Code geharmoniseerd systeem (HS)                | 8517620090                                        |
| Kleur van het product                       | Groen                                                                                                                 | Pallet brutobreedte                             | 120 cm                                            |
| Intern *                                    | ✓                                                                                                                     | Pallet brutolengte                              | 80 cm                                             |
| Land van herkomst                           | China                                                                                                                 | Pallet brutohoogte                              | 189,4 cm                                          |
|                                             |                                                                                                                       | Aantal (buitenste) hoofdverpakkingen per pallet | 19 stuk(s)                                        |
|                                             |                                                                                                                       | (Buitenste) hoofdverpakking breedte             | 490 mm                                            |
|                                             |                                                                                                                       | (Buitenste) hoofdverpakking lengte              | 340 mm                                            |
|                                             |                                                                                                                       | (Buitenste) hoofdverpakking hoogte              | 350 mm                                            |
|                                             |                                                                                                                       | (Buitenste) hoofdverpakking brutogewicht        | 15 kg                                             |
|                                             |                                                                                                                       | Hoeveelheid per (buitenste) hoofdverpakking     | 60 stuk(s)                                        |

Minimale systeemeisen

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ondersteunt Windows                   | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64 |
| Ondersteunt Linux                     | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Ondersteunde server operating systems | Windows Server 2012, Windows Server 2016                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

Eisen aan de omgeving

|                           |             |
|---------------------------|-------------|
| Bedrijfstemperatuur (T-T) | 0 - 45 °C   |
| Temperatuur bij opslag    | -40 - 85 °C |



4015867236246

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAY-2024. Prints or copies of Information are only valid on the printed Publication date