ATGBICS 320-2801 Dell Compatible Transceiver SFP 1000Base-SX (850nm, MMF, 550m)

Brand : ATGBICS Product code: 320-2801-C

Product name : 320-2801 Dell Compatible Transceiver SFP

1000Base-SX (850nm, MMF, 550m)



320-2801 Dell Compatible Transceiver SFP 1000Base-SX (850nm, MMF, 550m)

ATGBICS 320-2801 Dell Compatible Transceiver SFP 1000Base-SX (850nm, MMF, 550m):

ATGBICS 320-2801 1000Base-SX supports a distance of up to 550m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. It is a hot-swappable input/output device that plugs into a Gigabit Ethernet port/slot, linking the port with the fibre-optic network. Our product meets the specification of Dell 320-2801= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type * Fiber optic Maximum data transfer rate * 1000 Mbit/s Interface type * SFP Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector LC	1000 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 0.8 W
SFP transceiver standard	SX	Operational conditions	
Maximum transfer distance 550 m Navelength 850 nm Ethernet LAN Ethernet interface type Gigabit Ethernet Digital Diagnostics Monitoring	850 nm	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 95% 5 - 95%
(DDM) Wavelength-division multiplexing (WDM)	×	Weight & dimensions	
		Width	13.4 mm
Features		Depth	56.5 mm
reatures		· ·	
Product colour	Silver Metal	Height Weight	8.5 mm 20 g
	Silver Metal ✓	Height	8.5 mm
Product colour Housing material		Height Weight	8.5 mm
Product colour Housing material Plug and Play Hot-Plug support		Height Weight Packaging data Number of products included	8.5 mm 20 g



5056468702913

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.