ATGBICS ALL4750 Allnet Compatible Transceiver SFP 1000Base-SX (850nm, MMF, 550m)

Product code: ALL4750-C

Features

Brand : ATGBICS

Performance

Product name : ALL4750 Allnet Compatible Transceiver SFP 1000Base-SX (850nm, MMF, 550m)

ALL4750 Allnet Compatible Transceiver SFP 1000Base-SX (850nm, MMF, 550m)

ATGBICS ALL4750 Allnet Compatible Transceiver SFP 1000Base-SX (850nm, MMF, 550m):


ATGBICS ALL4750 1000Base-SX supports a distance of up to 550m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. It is a hot-swappable input/output device that plugs into a Gigabit Ethernet port/slot, linking the port with the fibre-optic network. Our product meets the specification of Allnet ALL4750= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.







SFP transceiver type * Fiber optic Certification CE, FCC, RoHS Maximum data transfer rate * 1000 Mbit/s Power SFP Interface type * Input voltage 3.3 V Single-mode fiber (SMF) supported × Maximum voltage 3.5 V Multi-mode fiber (MMF) supported 1 Power consumption (typical) 0.8 W LC Fiber optic connector **Operational conditions** SX SFP transceiver standard Maximum transfer distance 550 m Maximum operating temperature 70 °C Wavelength 850 nm Operating temperature (T-T) 0 - 70 °C -40 - 85 °C Ethernet LAN Storage temperature (T-T) 1 Ethernet interface type **Gigabit Ethernet** Operating relative humidity (H-H) 5 - 95% **Digital Diagnostics Monitoring** Storage relative humidity (H-H) 5 - 95% 1 (DDM) Weight & dimensions Wavelength-division multiplexing X (WDM) Width 13.4 mm Depth 56.5 mm Features 8.5 mm Height Product colour Silver Weight 20 g Housing material Metal Packaging data Plug and Play Hot-Plug support Number of products included 1 pc(s) Box Hot-swap Package type J Easy to install J Technical details Country of origin United Kingdom Sustainability compliance 1 Brand compatibility ALLNET Doesn't contain Lead Compliance certificates RoHS



5056468702326

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.