ATGBICS FCOPPER-SFP-100 Sixnet Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m)

Brand : ATGBICS Product code: FCOPPER-SFP-100-C

Product name : FCOPPER-SFP-100 Sixnet Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m)



FCOPPER-SFP-100 Sixnet Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m)

ATGBICS FCOPPER-SFP-100 Sixnet Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m):

ATGBICS FCOPPER-SFP-100 1000BASE-T SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Sixnet 100BASE-T SFP modules support 10/100 auto negotiation and auto MDI/MDIX. Our product meets the specification of Sixnet FCOPPER-SFP-100= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS FCOPPER-SFP-100 Sixnet Compatible Transceiver SFP 100Base-T (Copper RJ45, 100m). SFP transceiver type: Copper, Maximum data transfer rate: 100 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.5 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box



Performance		Features	
SFP transceiver type * Maximum data transfer rate * Interface type * Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported SFP transceiver standard Maximum transfer distance Ethernet LAN Ethernet interface type Copper ethernet cabling technology Auto MDI/MDI-X Digital Diagnostics Monitoring (DDM)	Copper 100 Mbit/s SFP X X TX 100 m Fast Ethernet 100BASE	Certification	CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical) Operational conditions	3.3 V 4 V 1.3 W
		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85%
Features		Weight & dimensions	
Product colour Housing material Plug and Play Hot-Plug support Hot-swap Easy to install Country of origin Brand compatibility	Silver Metal	Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 20 g
		Packaging data	
		Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability compliance Sustainability certificates Doesn't contain	√ RoHS Lead



5056468783660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.