## ATGBICS SFP-FE-SX-MM1310 Huawei Compatible Transceiver SFP, 100Base-FX (1310nm, MMF, 2km, DOM)

**Brand :** ATGBICS **Product code:** SFP-FE-SX-MM1310-C

**Product name :** SFP-FE-SX-MM1310 Huawei Compatible Transceiver SFP, 100Base-FX (1310nm, MMF, 2km, DOM)



SFP-FE-SX-MM1310 Huawei Compatible Transceiver SFP, 100Base-FX (1310nm, MMF, 2km, DOM)

ATGBICS SFP-FE-SX-MM1310 Huawei Compatible Transceiver SFP, 100Base-FX (1310nm, MMF, 2km, DOM):

ATGBICS SFP-FE-SX-MM1310 100Base-FX supports a distance of up to 2km over multi-mode fibre (MMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Huawei SFP-FE-SX-MM1310= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 100 Mbit/s  Interface type * SFP  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector  Fiber optic connector  LC  SFP transceiver standard  Maximum transfer distance  Wavelength  Ethernet LAN  Ethernet interface type  Copper ethernet cabling technology  Digital Diagnostics Monitoring (DDM)  Wavelength-division multiplexing (WDM)  Features  Product colour  Housing material  Plug and Play  Hot-Plug support  Hot-swap  Easy to install  Country of origin  Fiber optic 100 Mbit/s  FX  MAX  MAX  FX  MAX  MAX  FX  MAX  MA	100 Mbit/s SFP   LC FX	Brand compatibility Certification	Huawei CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 4 V 1.3 W
		Operational conditions	
	1310 nm  ✓ Fast Ethernet 100BASE  ✓	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight	70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85% 13.4 mm 56.5 mm 8.5 mm
	Metal	Packaging data	2 v g
	4	Number of products included Package type	1 pc(s) Box
	<b>√</b> United Kingdom	Technical details	
		Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468701732

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.