

ATGBICS VX\_00021 VSS Monitoring Compatible Transceiver SFP  
10/100/1000Base-T (RJ45, Copper, 100m)

Brand : ATGBICS

Product code: VX\_00021-C

Product name : VX\_00021 VSS Monitoring Compatible  
Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)



VX\_00021 VSS Monitoring Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

ATGBICS VX\_00021 VSS Monitoring Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m):

ATGBICS VX\_00021 SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. VSS Monitoring 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product meets the specification of VSS Monitoring VX\_00021= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



| Performance                          |                           | Features                          |               |
|--------------------------------------|---------------------------|-----------------------------------|---------------|
| SFP transceiver type *               | Copper                    | Certification                     | CE, FCC, RoHS |
| Maximum data transfer rate *         | 1000 Mbit/s               | Power                             |               |
| Interface type *                     | SFP                       | Input voltage                     | 3.3 V         |
| Single-mode fiber (SMF) supported    | ✗                         | Maximum voltage                   | 4 V           |
| Multi-mode fiber (MMF) supported     | ✗                         | Power consumption (typical)       | 1.3 W         |
| SFP transceiver standard             | TX                        | Operational conditions            |               |
| Maximum transfer distance            | 100 m                     | Maximum operating temperature     | 70 °C         |
| Ethernet LAN                         | ✓                         | Operating temperature (T-T)       | 0 - 70 °C     |
| Ethernet interface type              | Gigabit Ethernet          | Storage temperature (T-T)         | -40 - 85 °C   |
| Copper ethernet cabling technology   | 10BASE, 100BASE, 1000BASE | Operating relative humidity (H-H) | 5 - 85%       |
| Auto MDI/MDI-X                       | ✓                         | Storage relative humidity (H-H)   | 5 - 85%       |
| Digital Diagnostics Monitoring (DDM) | ✗                         | Weight & dimensions               |               |
| Features                             |                           | Width                             | 13.4 mm       |
| Product colour                       | Silver                    | Depth                             | 56.5 mm       |
| Housing material                     | Metal                     | Height                            | 8.5 mm        |
| Plug and Play                        | ✓                         | Weight                            | 20 g          |
| Hot-Plug support                     | ✓                         | Packaging data                    |               |
| Hot-swap                             | ✓                         | Number of products included       | 1 pc(s)       |
| Easy to install                      | ✓                         | Package type                      | Box           |
| Country of origin                    | United Kingdom            | Technical details                 |               |
| Brand compatibility                  | VSS Monitoring            | Sustainability compliance         | ✓             |
|                                      |                           | Sustainability certificates       | RoHS          |
|                                      |                           | Doesn't contain                   | Lead          |



5056468701251

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAY-2024. Prints or copies of Information are only valid on the printed Publication date